

**Multi Plus Putty**



**Description**

High quality two component polyester putty with fine grain composition for smoothing irregularities of different types of surfaces. The product is used in automotive refinishing.

**Application**

Universal polyester putty for eliminating car and commercial vehicle body imperfections.

**Characteristics**

- Excellent adhesion to a wide range of materials used for body construction in automotive industry
- Maximum stability on vertical surfaces
- No cracking on the edges by fine sanding
- Give a compact, smooth surface of top quality
- Intended for manual/machine dry sanding.

**Substrates**

Steel, galvanized steel, aluminum, fiberglass plastics, carbon fibre, polyester materials, OEM substrates\*.

VOC: 4 g/L  
EU limit value: 2004/42/IB(b)(250)

Articles	Description	Pcs. / pack
2-211-2000	2.0 kg (can), w/hardener	6
2-211-3000	3.0 kg (cartridge), w/hardener	4

Substrate pretreatment



Substrates to be treated must be cleaned, dried, degreased with C.A.R.FIT Silicone Remover and sanded.  
Sand steel, light metal and fiberglass with grit P80 – P120  
Sand old paintwork to bare metal with grit P80 – P120



Remove old thermoplastic coats (NC- or 1K Acrylic paints), synthetic resins as well as acid-containing products (e.g. Wash primer)\*

Application



Add 2 % by weight with hardener



Pot life: 3–4 min at 20 °C

Further treatment



Sand after ca. 25 min at 20 °C



Sand dry with grit P80 – P180

Technical data

Color                    grey  
Density                 1830 g/L

Storage



Keep away from direct sunlight

\*Do not apply on one component (etch and anticorrosive) primers and thermoplastics. Application on paintwork coatings is not recommended.