

# 1K Plastic Primer Spray



## DESCRIPTION

High quality primer spray for plastics treatment.

## APPLICATION

The product is used as an adhesion promoter for almost all plastics, except for polyethylene.

## CHARACTERISTICS

- Quick drying at room temperature
- Excellent adhesion to plastics
- Contains silver pigment for application control
- Can be overcoated with any waterborne and solvent-based topcoats

## SUBSTRATES

Most of plastics, polyester putty, sanded G.R.P, old / OEM paintworks.

| Articles   | Description | Pcs. / pack |
|------------|-------------|-------------|
| 4-435-0400 | 400 ml      | 6           |

## SUBSTRATE PRETREATMENT



Clean and degrease the plastic surface with C.A.R.FIT Silicone Remover. It is recommended to matt the surface and clean it again to improve adhesion

## APPLICATION



Shake thoroughly for at least 2 minutes



Apply the primer in maximum 2 thin coats  
Consumption: 1 spray can / ca. 2 – 3m<sup>2</sup>



Flash-off between layers: 3 – 5 min



Spraying distance: 25 – 30 cm  
 · Apply at room temperature. Optimal application temperature: 15 – 25°C  
 · Shake the spray can once more before application of each new coat  
 · After use, hold aerosol can upside down and spray briefly to clean the nozzle

## FURTHER TREATMENT



Air drying / 20°C  
 Overcoat after: ca. 10 – 15 min  
 Drying time depends on environment temperature, humidity and coating thickness



Apply subsequent materials according to plastic painting technology

## TECHNICAL DATA

|        |                   |
|--------|-------------------|
| Basis  | polyolefine resin |
| Colour | silver            |

## STORAGE



This is a pressurized container, do not expose to direct sunlight or store above 35°C