

High Gloss Clear Coat Spray

DESCRIPTION

High quality glossy Clear Coat for spot repairs of car body coatings.

APPLICATION

For spot repair in car refinishing and decorative finish of different surfaces.

CHARACTERISTICS

- Fast drying at room temperature
- Good coverage
- Excellent long-lasting gloss
- UV and weather resistant
- Anti-yellowing properties

SUBSTRATES

Waterborne and solvent-borne basecoats, OEM coatings, wood, metal, aluminum, glass, stone and various types of plastic.



Articles	Description	Pcs. / pack
7-201-0400	400 ml	6

SUBSTRATE PRETREATMENT



- Dry thoroughly and matt old coatings
- Dry and clean base coatings with tack cloth to remove overspray
- Clean and degrease metal, glass, stone or plastic surface with C.A.R.FIT Silicone Remover. Matt the surface if necessary

APPLICATION



Shake thoroughly for at least 2 min



Apply 2 – 3 thin coats
Consumption: 1 spray can / ca. 0.5 m²



Flash-off between layers: 3 – 5 min



- Spraying distance: 25 – 30 cm
- Apply at room temperature. Optimal application temperature: 15 – 25°C
- Shake the spray can once more before application of each new coat
- After use, hold aerosol can upside down and spray briefly to clean the nozzle

FURTHER TREATMENT



Air drying / 20°C
· dust dry: ca. 5-10 min · dry to touch: ca. 10-20 min · can be overcoated after 2 h
Drying time depends on environment temperature, humidity and coating thickness

TECHNICAL DATA

Basis	acrylic resin
Temperature resistance	up to 110°C

STORAGE



This is a pressurized container, do not expose to direct sunlight or store above 35°C