

# Fade-out Thinner Spray

## DESCRIPTION

Fade-out thinner for blending of clear coats and 2K paints during spot repairs. The product is specially designed to ensure the overspray blending into the coat, leaving no visible difference between the old and new paintwork and reducing amount of polishing works.

## APPLICATION

For small and spot repair in car refinishing.

## CHARACTERISTICS

- Ideal coating for spot repair
- Easy to apply
- Good dissolving ability
- Forms easy to polish transition area
- Considerably reduces amount of polishing works

## SUBSTRATES

Metal and plastic parts, polyester putties, primers, fillers, fully cured old or fresh coatings.



Articles	Description	Pcs. / pack
7-551-0400	400 ml	6

## APPLICATION



Shake thoroughly for at least 2 min



Apply C.A.R.FIT 2K clear coat according to TDS



Apply 1-3 coats of fade-out thinner immediately after application of 2K clear coat. Spraying distance: 25 cm



Flash-off between layers: 20-30 sec



It is recommended to apply C.A.R.FIT fade-out thinner within 10 cm distance inside and outside the edge areas

## FURTHER TREATMENT



Dry the clear coat according to TDS



Polish the transition area

## TECHNICAL DATA

Basis	special resins
Colour	transparent

## STORAGE



This is a pressurized container, do not expose to direct sunlight or store above 35°C