

C.A.R.FIT

TECHNICAL DATA SHEET

The C.A.R.FIT Fast Paint System (FPS) is a new and modern paint preparation system designed for mixing, filling and temporary storage of coatings. It provides an easy way for clean paint preparation ensuring time and material savings. FPS can be used for every type of the spray gun with the help of special adapters. Enables the storage and later use of the left over paint.

Technical data

| ITEM | | SPECIFICATION | | |
|----------------------|--|---------------|----------|--------------------------|
| | ITEM | MESH | CAPACITY | SET |
| FPS SET | 3-225-0125 | 125 microns | 650ML | 2 5 lids+25liners+12caps |
| | 3-225-0190 | 190 microns | 650ML | 2 5 lids+25liners+12caps |
| | 3-227-0125 | 125 microns | 650ML | 50lids+50liners+24caps |
| | 3-227-0190 | 190 microns | 650ML | 50lids+50liners+24caps |
| | 3-225-0002 | | | 1hard cup+1collar |
| OTHER DATA | | | | |
| Material | Lid & Hard cup = PP Filter mesh= Nylon Liner = LDPE | | | |
| Resistance | All are corrosion-resistant of paint & thinner Black colour liner and lid are UV-resistant. | | | |
| Melting point | Lid & Outer cup = 170°C Liner = 120°C (Max. Working temp. = 80°C) | | | |

C.A.R.F.I.T

