

# Plastic Putty



## DESCRIPTION

Two component high-plasticity polyester putty for plastic parts repair. Excellent adhesion to plastics, fast drying and easy sanding.

## APPLICATION

For repairs on plastic parts of cars and commercial vehicles.

## SUBSTRATES

Various kinds of plastic:

- ABS (acrylonitrile-butadiene-styrene copolymer)
- EP (epoxides/laminates)
- PA (polyamide)
- PBTP (polybutylene terephthalate)
- PC (polycarbonate)
- POM (polyoxymethylene)
- PP/EPDM (polypropylene-ethylene-propylene-diene monomer copolymer)
- PPO (polypropylene oxide)
- PUR (polyurethane) soft and hard
- PVC (polyvinyl chloride)

VOC: < 250 g/L  
EU limit value: 2004/42/IB(b)(250)

Articles	Description	Pcs. / pack
2-160-0500	0.5 kg, w/hardener	12
3-310-0120	Plastic Spreaders Red	50

## SUBSTRATE PRETREATMENT



Substrates to be treated must be cleaned, dried, degreased (e. g. with C.A.R.FIT Silicone Remover) and treated with suitable matting materials

## APPLICATION



Add 2–3% BPO Hardener of weight



Pot life: 4–5 min at 20°C

## FURTHER TREATMENT



20–30 min depending on ambient temperature



With P80–180



With P80–320 (intermediate sanding step of 100 grit should be observed)



- Substrate to be treated must be thoroughly cleaned, degreased and dried
- Prior to putty application, the substrate must be sanded/treated with matting abrasives
- Remove all old materials that have poor adhesion or have not fully dried
- Do not apply this product on thermoplastic coatings or etch/acid primers
- Prior to application, mix well with a hardener/catalyst
- Apply at a temperature no lower than +10°C

## TECHNICAL DATA

Colour	grey
Density	1858 g/L

## STORAGE



Keep away from direct sunlight