Silicone Remover «Strawberry»



DESCRIPTION

Strawberry scented eleaning compound based on organic solvents for initial cleaning of old / OEM coatings, primed and filled surfaces as well as plastics from tar, silicone, oil, grease, sanding dust and other contaminants.

APPLICATION

Surface cleaning prior to application of preparatory and refinishing materials and after sanding in car and commercial vehicle refinish.

CHARACTERISTICS

- $\cdot \mbox{ Removes tar, silicone, oil, grease, grinding dust and other contaminants}$
- · Non-toxic and does not contain chlorohydrocarbons
- · Strawberry odour
- · Ozone-friendly product.

SUBSTRATES

Metal and plastic parts, polyester putties, primers, fillers, fully cured old or fresh coatings.

VOC: max 781 g/L EU limit value: 2004/42/IIB(a)(850

ш	Articles	Description	Pcs. / pack
	7-551-1000	11	6
	7-551-5000	5 L	3

SUBSTRATE PRETREATMENT



Do not use the product on solvent-sensitive substrates, e. g. thermoplastic coatings.

APPLICATION



Clean the substrate with C.A.R.FIT Silicone Remover Strawberry Apply with a spray gun, a cloth or a sponge



- \cdot Do not allow to dry on the substrate being treated
- Remove any remaining residue with a cleaning cloth

TECHNICAL DATA

Density

711-781 g/L

Shelf Life: 3 Years