

Stone Chip Protection Spray



DESCRIPTION

Stone chip spray is ideal coating for underbody protection from road gravel. The product forms durable elastic film with anticorrosion and sound deadening properties ensuring reliable protection of wheel housings and chassis of vehicles.

APPLICATION

For treating of car and commercial vehicle bodies.

CHARACTERISTICS

- Corrosion protection and sound deadening
- Excellent adhesion
- Long-lasting elasticity
- Good resistance to weather effects, abrasion, weak acids and bases

SUBSTRATES

Various metal surfaces, primed metal parts, fully cured old / OEM coatings.

Articles	Description	Pcs. / pack
5-601-0500	500 ml, black	6
5-602-0500	500 ml, grey	6

SUBSTRATE PRETREATMENT



Clean and degrease the surface with C.A.R.FIT Silicone Remover

APPLICATION



Shake thoroughly for at least 2 minutes



Apply a few coats



Flash-off between layers: 3 – 5 min



- Spraying distance: 30 cm
- Apply at room temperature. Optimal application temperature: 15 – 25°C
- After use, hold aerosol can upside down and spray briefly to clean the nozzle
- Fresh material can be removed with a thinner, dry product can be removed mechanically

FURTHER TREATMENT



Air drying / 20°C

· dust dry: ca. 30 min

· overcoat after ca. 1 h

Drying time depends on environment temperature, humidity and coating thickness

TECHNICAL DATA

Basis	rubber
Colour	black, grey
Salt spray test (DIN50021)	Ri 0 / 240 hours / 250 µ

STORAGE



This is a pressurized container, do not expose to direct sunlight or store above 35°C