

Underbody Protection Bitumen Spray



DESCRIPTION

High quality bitumen spray for vehicle underbody protection.

APPLICATION

For treatment of car and commercial vehicle bodies.

CHARACTERISTICS

- Remains flexible after drying
- Excellent adhesion to metals
- Good resistance to weather effects, weak acids and bases
- Reliable corrosion protection
- Sound-absorbing

SUBSTRATES

Various metal surfaces, primed metal parts, fully cured old / OEM coatings.


Articles	Description	Pcs. / pack
5-400-0500	500 ml	6

SUBSTRATE PRETREATMENT



- Clean and degrease the surface with C.A.R.FIT Silicone Remover
- Remove old coating and sand corrosion spots with grit P80 – P240
- Again clean and degrease the surface with C.A.R.FIT Silicone Remover and thoroughly dry it

APPLICATION



Shake thoroughly for at least 2 min



Apply a few coats

Flash-off between layers: 3 – 5 min

- Spraying distance: 25 cm
- Do not apply on chrome-plated surfaces
- Apply at room temperature. Optimal application temperature: 15 – 25°C
- Shake the spray can once more before application of each new coat
- After use, hold aerosol can upside down and spray briefly to clean the nozzle
- Maximum heat-resistance and fuel-resistance is achieved after stoving at 160 – 200°C for ca. 30 min

FURTHER TREATMENT



Dust dry: ca. 60 min / 20°C

Drying time depends on environment temperature, humidity and coating thickness

TECHNICAL DATA

Basis	bitumen
Colour	black

STORAGE



This is a pressurized container, do not expose to direct sunlight or store above 35°C