

## Gun Cleaner

**DESCRIPTION**

Effective solvent-based cleaning agent with high dissolving ability. It is recommended to use the product together with automatic spray gun washing machines to increase its performance.

**APPLICATION**

The product is used for cleaning of spray guns and other tools from residues of paintwork materials.

**CHARACTERISTICS**

- High dissolving ability
- Efficient removal of paintwork materials, dirt, grease, oil, silicone, waxes, etc.
- Fast drying

**SUBSTRATES**

Metal parts and surfaces.

VOC: max 880 g/L

EU limit value: 2004/42/116(e) (850)

Articles	Description	Pcs. / pack
8-102-5000	5 L	1

**APPLICATION**

- Use automatic spray gun washing machines for spray gun cleaning
- strictly comply with safety rules and regulations during work with Gun Cleaner
- Do not allow the product to dry on the substrate being treated
- Remove any residues of the product with a cleaning cloth

**TECHNICAL DATA**

Density 830–880 g/L

**STORAGE**

Keep away from direct sunlight



## Universal polishing compound

**DESCRIPTION**

Universal Polishing Compound is a very efficient 1-step detailing compound offering a wide range of applications on all common paint systems. Together with excellent cutting performance the product provides superior mirror-like gloss. Even holograms and swirl marks on dark paint surfaces can be polished out easily.

**APPLICATION**

Polishing of car and truck coatings.

**CHARACTERISTICS**

- Removes deep scratches, refreshes weathered surfaces and creates high gloss in one single step
- Highly effective with conventional and scratch-resistant paintworks
- Suitable for both manual and machine polishing
- High gloss level
- Easy to use.

VOC: = 150.7 g/L

Articles	Description	Pcs. / pack
5-101-0250/1000	Tube, 250 ml / 1000 ml	15/8

**SUBSTRATE PRETREATMENT**

Clean the surface thoroughly from dust using sponge with water and from fat and oil using a degreaser. Dry the surface before application of the product.

**APPLICATION**

Shake well before applying.

**Machine polishing**

Start polishing using an orange polishing disk and finish using a black one or use woolen polishing disk as a universal solution. Polishing pad rotation speed: 1500-2000 /min.

Apply some amount of the polishing to a new and dry polishing pad to make it impregnated. Then apply the necessary quantity of the product to an area of 50x50 cm. Distribute the paste evenly on the surface before polishing. Polish with small or medium pressure on the machine. Decrease the pressure as the paste becomes drier. Wipe the surface and check whether all the sanding marks are removed. Apply the product and polish again if necessary.

**Manual polishing**

Apply the paste on the surface using a cloth. Polish the surface using a clean polishing cloth.

**NOTES**

- Do not polish objects contacting with food or drinking water.
- Shake before use.
- Do not apply at direct sunlight.

**TECHNICAL DATA**

Colour	white
Density	ca 1000 g/L
Abrasive	aluminum oxide
Cutting ability	5.5
Gloss level	4.5

**STORAGE**

Protect from freezing!  
Keep away from direct sunlight.  
Store at temperatures from +5 to +25°C.