

SAFETY DATA SHEET

C.A.R.FIT Fade Out Spray

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

C.A.R.FIT Fade Out Spray

Other names / Synonyms

C.A.R.FIT Fade Out Spray

Product no.

7-551-0400

▼ Unique formula identifier (UFI)

X9E9-0CNC-S246-M18V

1.2. Relevant identified uses of the substance or mixture and uses advised against

▼ Relevant identified uses of the substance or mixture

adhesion promoter

Restricted to professional users.

Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	Description
PC 9a	Coatings and Paints, Fillers, Putties, Thinners
Process category	Description
PROC 7	Industrial spraying
PROC 11	Non industrial spraying

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

August Handel GmbH

Ahornstraße 12

14959 Trebbin

Germany

+49 (0)33731 70 79 60

www.augusthandel.com

E-mail

info@augusthandel.com

Revision

04/08/2025

SDS Version

2.0

Date of previous version

06/06/2024 (1.0)

1.4. ▼ Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Scotland - Dial 111 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.
STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)
May cause drowsiness or dizziness. (H336)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Do not spray on an open flame or other ignition source. (P211)
Do not pierce or burn, even after use. (P251)
Do not breathe spray. (P260)

Response

-

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

▼ Disposal

Dispose of contents/container in accordance with regional regulation.
(P501)

▼ Hazardous substances

n-butyl acetate
2-methoxy-1-methylethyl acetate
ethyl acetate

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

UFI: X9E9-0CNC-S246-M18V

VOC

VOC content: 731,4 g/L
MAXIMUM VOC CONTENT (Phase II, category B/e: 840 g/L)

2.3. Other hazards

▼ Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
dimethyl ether	CAS No.: 115-10-6 EC No.: 204-065-8 UK-REACH: Index No.: 603-019-00-8	50 - <75%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	[1]
n-butyl acetate	CAS No.: 123-86-4 EC No.: 204-658-1 UK-REACH: Index No.: 607-025-00-1	20 - <25%	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336	[1]
2-methoxy-1-methylethyl acetate	CAS No.: 108-65-6 EC No.: 203-603-9 UK-REACH: Index No.:	5 - <10%	Flam. Liq. 3, H226 STOT SE 3, H336	[1]
ethyl acetate	CAS No.: 141-78-6 EC No.: 205-500-4 UK-REACH: Index No.: 607-022-00-5	5 - <10%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
reaction mass of ethylbenzene and xylene	CAS No.: EC No.: 905-588-0 UK-REACH: Index No.:	2,5 - <5%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER/doctor if you feel unwell.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. ▼ Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

7.1. Precautions for safe handling

Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.
Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼ Control parameters

dimethyl ether

Long term exposure limit (8 hours) (ppm): 400
Long term exposure limit (8 hours) (mg/m³): 766
Short term exposure limit (15 minutes) (ppm): 500
Short term exposure limit (15 minutes) (mg/m³): 958

n-butyl acetate

Long term exposure limit (8 hours) (ppm): 150
Long term exposure limit (8 hours) (mg/m³): 724
Short term exposure limit (15 minutes) (ppm): 200
Short term exposure limit (15 minutes) (mg/m³): 966

2-methoxy-1-methylethyl acetate

Long term exposure limit (8 hours) (ppm): 50
Long term exposure limit (8 hours) (mg/m³): 274
Short term exposure limit (15 minutes) (ppm): 100
Short term exposure limit (15 minutes) (mg/m³): 548

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

ethyl acetate

Long term exposure limit (8 hours) (ppm): 200
Short term exposure limit (15 minutes) (ppm): 400

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

2-methoxy-1-methylethyl acetate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	320 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	796 mg/kg bw/day
Long term – Local effects - General population	Inhalation	33 mg/m ³
Long term – Systemic effects - General population	Inhalation	33 mg/m ³
Long term – Systemic effects - Workers	Inhalation	275 mg/m ³

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Short term – Local effects - Workers	Inhalation	550 mg/m ³
Long term – Systemic effects - General population	Oral	36 mg/kg bw/day
Short term – Systemic effects - General population	Oral	500 mg/kg bw/day

dimethyl ether

Duration:	Route of exposure:	DNEL:
Long term	-	
Short term	-	
Long term – Systemic effects - General population	Inhalation	471 mg/m ³
Long term – Systemic effects - Workers	Inhalation	1894 mg/m ³

ethyl acetate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	37 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	63 mg/kg bw/day
Long term – Local effects - General population	Inhalation	367 mg/m ³
Long term – Local effects - Workers	Inhalation	734 mg/m ³
Long term – Systemic effects - General population	Inhalation	367 mg/m ³
Long term – Systemic effects - Workers	Inhalation	734 mg/m ³
Short term – Local effects - General population	Inhalation	734 mg/m ³
Short term – Local effects - Workers	Inhalation	1468 mg/m ³
Short term – Systemic effects - General population	Inhalation	734 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1468 mg/m ³
Long term – Systemic effects - General population	Oral	4.5 mg/kg bw/day

n-butyl acetate

Duration:	Route of exposure:	DNEL:
Long term	-	
Short term	-	
Long term – Systemic effects - General population	Dermal	3.4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	7 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	6 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	11 mg/kg bw/day
Long term – Local effects - General population	Inhalation	35.7 mg/m ³
Long term – Local effects - Workers	Inhalation	300 mg/m ³
Long term – Systemic effects - General population	Inhalation	12 mg/m ³
Long term – Systemic effects - Workers	Inhalation	48 mg/m ³
Short term – Local effects - General population	Inhalation	300 mg/m ³
Short term – Local effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - General population	Inhalation	300 mg/m ³
Short term – Systemic effects - Workers	Inhalation	600 mg/m ³
Long term – Systemic effects - General population	Oral	2 mg/kg bw/day
Short term – Systemic effects - General population	Oral	2 mg/kg bw/day

▼ PNEC

2-methoxy-1-methylethyl acetate

Route of exposure:	Duration of Exposure:	PNEC:
--------------------	-----------------------	-------

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Freshwater	635 µg/L
Freshwater sediment	3.29 mg/kg
Intermittent release (freshwater)	6.35 mg/L
Marine water	63.5 µg/L
Marine water sediment	329 µg/kg
Sewage treatment plant	100 mg/L
Soil	290 µg/kg
dimethyl ether	
Route of exposure:	Duration of Exposure:
Freshwater	155 µg/L
Freshwater sediment	681 µg/kg
Intermittent release (freshwater)	1.549 mg/L
Marine water	16 µg/L
Marine water sediment	69 µg/kg
Sewage treatment plant	160 mg/L
Soil	45 µg/kg
ethyl acetate	
Route of exposure:	Duration of Exposure:
Freshwater	240 µg/L
Freshwater sediment	1.15 mg/kg
Intermittent release (freshwater)	1.65 mg/L
Marine water	24 µg/L
Marine water sediment	115 µg/kg
Predators	200 mg/kg
Sewage treatment plant	650 mg/L
Soil	148 µg/kg
n-butyl acetate	
Route of exposure:	Duration of Exposure:
Freshwater	180 µg/L
Freshwater sediment	981 µg/kg
Intermittent release (freshwater)	360 µg/L
Marine water	18 µg/L
Marine water sediment	98.1 µg/kg
Sewage treatment plant	35.6 mg/L
Soil	90.3 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure


No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

▼ Respiratory Equipment

Type	Class	Colour	Standards	
Combination filter A2P3	Class 2/3	Brown/White	EN14387	
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.				

▼ Skin protection

Recommended	Type/Category	Standards
No specific requirements.	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
No special when used as intended	-	-	-

▼ Eye protection

Type	Standards
No special when used as intended.	-

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

Colourless

▼ Odour / Odour threshold

Solvent

▼ pH

Not applicable - water solubility < 1 mg/L @ 20°C

Density (g/cm³)

0.7 (20 °C)

Kinematic viscosity

No data available

Particle characteristics

No data available

Phase changes

▼ Melting point/Freezing point (°C)

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

No data available

Softening point/range (°C)

Does not apply to aerosols.

Boiling point (°C)

Not applicable - product is an aerosol

Vapour pressure

4000 hPa (20 °C)

Relative vapour density

No data available

▼ Decomposition temperature (°C)

No data available

Data on fire and explosion hazards

Flash point (°C)

Not applicable - product is an aerosol

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

240

Lower and upper explosion limit (% v/v)

1.2 - 26.2

Solubility

▼ Solubility in water

Practically insoluble

n-octanol/water coefficient (LogKow)

No data available

Solubility in fat (g/L)

No data available

9.2. Other information

VOC (g/L)

731,4

Other physical and chemical parameters

No data available.

▼ Oxidizing properties

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance

dimethyl ether

Species:

Rat

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Route of exposure: Inhalation
 Test: LC50
 Result: 308 mg/m³ ·

Product/substance n-butyl acetate
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: 10768 mg/kg ·

Product/substance n-butyl acetate
 Species: Mouse
 Route of exposure: Oral
 Test: LD50
 Result: 6 mg/kg ·

Product/substance n-butyl acetate
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50
 Result: 21,0 mg/l 4h ·

Product/substance n-butyl acetate
 Species: Rat
 Route of exposure: Dermal
 Test: LD50
 Result: 10760 mg/kg ·

Product/substance n-butyl acetate
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: 10770 mg/kg ·

Product/substance n-butyl acetate
 Species: Rabbit
 Route of exposure: Dermal
 Test: LD50
 Result: >17600 mg/kg ·

Product/substance n-butyl acetate
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50
 Result: >21,0 mg/m³ ·

Product/substance ethyl acetate
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: 6100 mg/kg ·

Product/substance ethyl acetate
 Species: Rabbit
 Route of exposure: Dermal
 Test: LD50
 Result: > 20000 mg/kg ·

Product/substance ethyl acetate
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Result: 58 mg/l ·

Product/substance ethyl acetate
Species: Rabbit
Route of exposure: Oral
Test: LD50
Result: 5620 mg/kg ·

Product/substance ethyl acetate
Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >18000 mg/kg ·

Product/substance ethyl acetate
Species: Rat
Route of exposure: Inhalation
Test: LC50
Result: 1600 mg/m³ ·

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

None known.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance dimethyl ether
Species: Daphnia
Duration: 48 hours

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Test: EC50
Result: >4000 mg/l ·

Product/substance n-butyl acetate
Species: Fish
Duration: 96 hours
Test: LC50
Result: 18 mg/L ·

Product/substance n-butyl acetate
Species: Fish
Duration: 96 hours
Test: LC50
Result: 100 mg/L ·

Product/substance n-butyl acetate
Species: Fish
Duration: 96 hours
Test: LC50
Result: 185 mg/L ·

Product/substance n-butyl acetate
Species: Fish
Duration: 96 hours
Test: LC50
Result: 62 mg/L ·

Product/substance n-butyl acetate
Species: Crustacean
Duration: 48 hours
Test: EC50
Result: 32 mg/L ·

Product/substance n-butyl acetate
Species: Daphnia
Duration: 48 hours
Test: EC50
Result: 44 mg/L ·

Product/substance n-butyl acetate
Species: Algae
Duration: 96 hours
Test: EC50
Result: 320 mg/L ·

Product/substance n-butyl acetate
Species: Daphnia
Duration: 24 hours
Test: LC50
Result: 205 mg/L ·

Product/substance ethyl acetate
Species: Algae
Duration: 72 hours
Test: EC50
Result: > 100 mg/l ·

Product/substance ethyl acetate
Species: Daphnia
Duration: 48 hours
Test: EC50
Result: 165 mg/l ·

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance ethyl acetate
Species: Fish
Duration: 96 hours
Test: LC50
Result: 212 mg/l ·

Product/substance ethyl acetate
Species: Daphnia
Duration: 24 hours
Test: EC50
Result: 2500 mg/L ·

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 3 - Flammable

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.


EWC code

20 01 13* Solvents
15 01 04 Metallic packaging



Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information .

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information
IATA	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information

* Packing group

** Environmental hazards

▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

-

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

▼ REACH, Annex XVII

dimethyl ether is subject to UK-REACH restrictions (entry 40).

n-butyl acetate is subject to UK-REACH restrictions (entry 40).

2-methoxy-1-methylethyl acetate is subject to UK-REACH restrictions (entry 40).

ethyl acetate is subject to UK-REACH restrictions (entry 40).

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

reaction mass of ethylbenzene and xylene is subject to UK-REACH restrictions (entry 40).

Additional information

Not applicable.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).

Control of Major Accident Hazards (COMAH) Regulations 2015.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H373, Repeated exposure may cause skin dryness or cracking.

H220, Extremely flammable gas.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H280, Contains gas under pressure; may explode if heated.

H304, May be fatal if swallowed and enters airways.

H312, Harmful in contact with skin.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

H373, May cause damage to organs through prolonged or repeated exposure.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC 7 = Industrial spraying

PROC 11 = Non industrial spraying

PC 9a = Coatings and Paints, Fillers, Putties, Thinners

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWG = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard to health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

S. Grade

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en