

SAFETY DATA SHEET

C.A.R.FIT Paint Remover Spray

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

C.A.R.FIT Paint Remover Spray

Other names / Synonyms

C.A.R.FIT Paint Remover Spray

Product no.

7-553-0400

Unique formula identifier (UFI)

1U50-R0MG-P00Q-14EM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Paint remover

Restricted to professional users.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

August Handel GmbH

Ahornstraße 12

14959 Trebbin

Germany

+49 (0)33731 70 79 60

www.augusthandel.com

E-mail

info@augusthandel.com

Revision

05/08/2025

SDS Version

1.0

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 111 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Irrit. 2; H319, Causes serious eye irritation.

2.2. Label elements

Hazard pictogram(s)

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

May cause an allergic skin reaction. (H317)

Causes serious eye irritation. (H319)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Read label before use. (P103)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not spray on an open flame or other ignition source. (P211)

Do not pierce or burn, even after use. (P251)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. (P305+P351+P338)

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

Dispose of contents/container in accordance with local regulation.

/ in accordance with regional regulation.

/ in accordance with national regulation.

/ in accordance with international regulation.

(P501)

Hazardous substances

benzyl alcohol

Additional labelling

UFI: 1U50-R0MG-P00Q-14EM

VOC

VOC content: <750 g/L

MAXIMUM VOC CONTENT (Phase II, category B/a1: 850 g/L)

2.3. Other hazards

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
dimethyl ether	CAS No.: 115-10-6 EC No.: 204-065-8 UK-REACH: Index No.: 603-019-00-8	25 - 50%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	[1]
benzyl alcohol	CAS No.: 100-51-6 EC No.: 202-859-9	25 - 50%	Acute Tox. 4, H302 Eye Irrit. 2, H319	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

	UK-REACH: Index No.: 603-057-00-5		Acute Tox. 4, H332	
ethanol ethyl alcohol	CAS No.: 64-17-5 EC No.: 200-578-6 UK-REACH: Index No.: 603-002-00-5	10 - 25%	Flam. Liq. 2, H225	
Isotridecanol, ethoxylated	CAS No.: 69011-36-5 EC No.: 500-241-6 UK-REACH: Index No.:	<2,5%	Eye Irrit. 2, H319 Aquatic Chronic 3, H412	[19]
butanone ethyl methyl ketone	CAS No.: 78-93-3 EC No.: 201-159-0 UK-REACH: Index No.: 606-002-00-3	<1%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact

The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

2. Material appears to be discolored.
 3. Deterioration or distortion of storage container.
 4. Thermal shock (sunlight).
 5. Age of material exceeds recommended storage time.
- Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.
Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dimethyl ether

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 766

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 958

ethanol ethyl alcohol

Long term exposure limit (8 hours) (ppm): 1000

Long term exposure limit (8 hours) (mg/m³): 1920

butanone ethyl methyl ketone

Long term exposure limit (8 hours) (ppm): 200

Long term exposure limit (8 hours) (mg/m³): 600

Short term exposure limit (15 minutes) (ppm): 300

Short term exposure limit (15 minutes) (mg/m³): 899

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

benzyl alcohol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	8 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	20 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	40 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	5.4 mg/m ³
Long term – Systemic effects - Workers	Inhalation	22 mg/m ³

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Short term – Systemic effects - General population	Inhalation	27 mg/m ³
Short term – Systemic effects - Workers	Inhalation	110 mg/m ³
Long term – Systemic effects - General population	Oral	4 mg/kg bw/day
Short term – Systemic effects - General population	Oral	20 mg/kg bw/day

butanone ethyl methyl ketone

Duration:	Route of exposure:	DNEL:
Long term	-	
Short term	-	
Long term – Systemic effects - General population	Dermal	412 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	1161 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	106 mg/m ³
Long term – Systemic effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - General population	Inhalation	450 mg/m ³
Short term – Systemic effects - Workers	Inhalation	900 mg/m ³
Long term – Systemic effects - General population	Oral	31 mg/kg bw/day

dimethyl ether

Duration:	Route of exposure:	DNEL:
Long term	-	
Short term	-	
Long term – Systemic effects - General population	Inhalation	471 mg/m ³
Long term – Systemic effects - Workers	Inhalation	1894 mg/m ³

ethanol ethyl alcohol

Duration:	Route of exposure:	DNEL:
Long term	-	
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	114 mg/m ³
Long term – Systemic effects - Workers	Inhalation	380 mg/m ³
Short term – Local effects - General population	Inhalation	950 mg/m ³
Short term – Local effects - Workers	Inhalation	1900 mg/m ³
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

Isotridecanol, ethoxylated

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	93.8 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	263 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	6.53 mg/m ³
Long term – Systemic effects - Workers	Inhalation	37 mg/m ³
Long term – Systemic effects - General population	Oral	2.5 mg/kg bw/day

PNEC

benzyl alcohol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1-1.02 mg/L
Freshwater sediment		5.27 mg/kg

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Intermittent release (freshwater)	2.3 mg/L
Marine water	100-102 µg/L
Marine water sediment	527 µg/kg
Sewage treatment plant	39 mg/L
Soil	456 µg/kg
butanone ethyl methyl ketone	
Route of exposure:	Duration of Exposure: PNEC:
Freshwater	55.8 mg/L
Freshwater sediment	284.74 mg/kg
Intermittent release (freshwater)	55.8 mg/L
Marine water	55.8 mg/L
Marine water sediment	284.7 mg/kg
Predators	1 g/kg
Sewage treatment plant	709 mg/L
Soil	22.5 mg/kg
dimethyl ether	
Route of exposure:	Duration of Exposure: PNEC:
Freshwater	155 µg/L
Freshwater sediment	681 µg/kg
Intermittent release (freshwater)	1.549 mg/L
Marine water	16 µg/L
Marine water sediment	69 µg/kg
Sewage treatment plant	160 mg/L
Soil	45 µg/kg
ethanol ethyl alcohol	
Route of exposure:	Duration of Exposure: PNEC:
Freshwater	960 µg/L
Freshwater sediment	3.6 mg/kg
Intermittent release (freshwater)	2.75 mg/L
Marine water	790 µg/L
Marine water sediment	2.9 mg/kg
Predators	380-720 mg/kg
Sewage treatment plant	580 mg/L
Soil	630 µg/kg
Isotridecanol, ethoxylated	
Route of exposure:	Duration of Exposure: PNEC:
Freshwater	4.36 µg/L
Freshwater sediment	119.4 µg/kg
Intermittent release (freshwater)	5.44 µg/L
Intermittent release (marine water)	544 ng/L
Marine water	436 ng/L
Marine water sediment	11.94 µg/kg
Sewage treatment plant	4.35 mg/L

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Soil	21.3 µg/kg
------	------------

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.			



Skin protection

Recommended	Type/Category	Standards
No specific requirements.	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Gloves	-	-	EN374



Eye protection

Type	Standards
Safety glasses with side shields.	EN ISO 16321-1



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

No data available

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Odour / Odour threshold

Characteristic

pH

No data available

Density (g/cm³)

0.815 (20 °C)

Kinematic viscosity

No data available

Particle characteristics

No data available

Phase changes

Melting point/Freezing point (°C)

No data available

Softening point/range (°C)

Does not apply to aerosols.

Boiling point (°C)

-24.9

Vapour pressure

5200 hPa (20 °C)

Relative vapour density

No data available

Decomposition temperature (°C)

No data available

Data on fire and explosion hazards

Flash point (°C)

<0

Test method: EN ISO 1523

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

235

Lower and upper explosion limit (% v/v)

1.3 - 18.6

Solubility

Solubility in water

Practically insoluble

n-octanol/water coefficient (LogKow)

No data available

Solubility in fat (g/L)

No data available

9.2. Other information

Evaporation rate (n-butylacetate = 100)

Not applicable - product is an article

VOC (g/L)

<750

Other physical and chemical parameters

No data available.

Oxidizing properties

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	dimethyl ether
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	308 mg/m ³ ·

Product/substance	ethanol ethyl alcohol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	7060 mg/kg ·

Product/substance	ethanol ethyl alcohol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg ·

Product/substance	ethanol ethyl alcohol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	20000 mg/m ³ ·

Product/substance	butanone ethyl methyl ketone
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	2737 mg/kg ·

Product/substance	butanone ethyl methyl ketone
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	6480 mg/kg ·

Product/substance	butanone ethyl methyl ketone
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	34 mg/m ³ ·

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	dimethyl ether
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	>4000 mg/l ·

Product/substance	ethanol ethyl alcohol
Species:	Daphnia
Duration:	24 hours
Test:	EC50
Result:	>100 mg/l ·

Product/substance	ethanol ethyl alcohol
Species:	Crustacean
Duration:	48 hours
Test:	LC50
Result:	9000 mg/l ·

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 6 - Acute toxicity

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

15 01 04

Metallic packaging

08 01 11*

Waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

-

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

Regulation on drug precursors

butanone ethyl methyl ketone is included (Category 3)

REACH, Annex XVII

dimethyl ether is subject to UK-REACH restrictions (entry 40).

ethanol ethyl alcohol is subject to UK-REACH restrictions (entry 40).

butanone ethyl methyl ketone is subject to UK-REACH restrictions (entry 40).

Additional information

Not applicable.

Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).

Control of Major Accident Hazards (COMAH) Regulations 2015.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

The Controlled Drugs (Drug Precursors) Regulations 2008.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

H314, Causes severe skin burns and eye irritation.

H220, Extremely flammable gas.

H225, Highly flammable liquid and vapour.

H280, Contains gas under pressure; may explode if heated.

H302, Harmful if swallowed.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H336, May cause drowsiness or dizziness.

H412, Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

S. Grade

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

data sheet cannot be used as a product specification.
Country-language: GB-en