SAFETY DATA SHEET

C.A.R.FIT Silicone Remover Spray "Strawberry"

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name
C.A.R.FIT Silicone Remover Spray "Strawberry"

Other names / Synonyms
C.A.R.FIT Silicone Remover Spray "Strawberry"

Product no.
7-500-0400

Unique formula identifier (UFI)
NM3V-6MPE-W894-1PYG

1.2. Relevant identified uses of the substance or mixture and uses advised against

▼Relevant identified uses of the substance or mixture
Preparation
Restricted to professional users.

Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process category	Description
PROC 7	Industrial spraying
PROC 11	Non industrial spraying

▼Uses advised against
None known.

1.3. Details of the supplier of the safety data sheet

Company and address
August Handel GmbH
Ahornstraße 12
14959 Trebbin
Germany
+49 (0)33731 70 79 60
www.augusthandel.com

E-mail
info@augusthandel.com

Revision
13/05/2025

SDS Version
4.0

Date of previous version
02/12/2024 (3.0)

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 112 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Eye Irrit. 2; H319, Causes serious eye irritation.
STOT SE 3; H336, May cause drowsiness or dizziness.
Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)

Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)
May be fatal if swallowed and enters airways. (H304)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)
Toxic to aquatic life with long lasting effects. (H411)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Do not spray on an open flame or other ignition source. (P211)
Do not pierce or burn, even after use. (P251)
Do not breathe spray. (P260)

Response

-

Storage

Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

Dispose of contents/container in accordance with regional regulation
(P501)

Hazardous substances

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
propan-2-ol isopropyl alcohol isopropanol

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

UFI: NM3V-6MPE-W894-1PYG

▼VOC

VOC content: 698,6 g/L
MAXIMUM VOC CONTENT (Phase II, category B/e: 840 g/L)

2.3. Other hazards

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	CAS No.: EC No.: 920-750-0 UK-REACH: Index No.:	50 - <75%	EUH066 Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411	
propane	CAS No.: 74-98-6 EC No.: 200-827-9 UK-REACH: Index No.: 601-003-00-5	12,5 - <20%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	
propan-2-ol isopropyl alcohol isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: Index No.: 603-117-00-0	10 - <12,5%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
butane	CAS No.: 106-97-8 EC No.: 203-448-7 UK-REACH: Index No.: 601-004-01-8	5 - <10%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	
isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 UK-REACH: Index No.: 601-004-00-0	5 - <10%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a

doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2)

5.3. ▼Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.
Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.
The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.
Avoid direct contact with the product.
Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:
1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.
Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propan-2-ol isopropyl alcohol isopropanol
Long term exposure limit (8 hours) (ppm): 400
Long term exposure limit (8 hours) (mg/m^3): 999
Short term exposure limit (15 minutes) (ppm): 500
Short term exposure limit (15 minutes) (mg/m^3): 1250

butane
Long term exposure limit (8 hours) (ppm): 600
Long term exposure limit (8 hours) (mg/m^3): 1450
Short term exposure limit (15 minutes) (ppm): 750
Short term exposure limit (15 minutes) (mg/m^3): 1810
Annotations:
Carc1 = Capable of causing cancer and/or heritable genetic damage if it contains more than 0.1% of buta-1,3-diene.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

butane

Duration:	Route of exposure:	DNEL:
Long term	-	
Short term	-	

propan-2-ol isopropyl alcohol isopropanol

Duration:	Route of exposure:	DNEL:
Long term	-	
Short term	-	
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m³
Long term – Systemic effects - Workers	Inhalation	500 mg/m³
Short term – Systemic effects - General population	Inhalation	178 mg/m³
Short term – Systemic effects - Workers	Inhalation	1000 mg/m³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

PNEC

propan-2-ol isopropyl alcohol isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release (freshwater)		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Predators		160 mg/kg
Sewage treatment plant		2.251 g/L
Soil		28 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Provide adequate general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards	
Combination filter A2P3	Class 2/3	Brown/White	EN14387	
In case of brief exposure or low pollution use				

Type	Class	Colour	Standards
respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.			

Skin protection

Recommended	Type/Category	Standards
No specific requirements.	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Butyl	0.4	> 480	EN374-2, EN374-3, EN388

Eye protection

Type	Standards
Safety glasses with side shields.	EN ISO 16321-1

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state
Aerosol

Colour
Colourless

Odour / Odour threshold
Aromatic

pH
No data available

Density (g/cm^3)
0.7 (20 °C)

Kinematic viscosity
No data available

Particle characteristics
No data available

Phase changes

Melting point/Freezing point (°C)
No data available

Softening point/range (°C)
Does not apply to aerosols.

Boiling point (°C)
Not applicable - product is an aerosol

Vapour pressure
3500 hPa (20 °C)

Relative vapour density
No data available

Decomposition temperature (°C)
No data available

Data on fire and explosion hazards

Flash point (°C)
Not applicable - product is an aerosol
Flammability (°C)
The material is ignitable.
Auto-ignition temperature (°C)
>200
Lower and upper explosion limit (% v/v)
0.6 - 13
Solubility
Solubility in water
Practically insoluble
n-octanol/water coefficient (LogKow)
No data available
Solubility in fat (g/L)
No data available
9.2. Other information
Evaporation rate (n-butylacetate = 100)
Not applicable - product is an article
VOC (g/L)
698,6
Other physical and chemical parameters
No data available.
Oxidizing properties
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available.
10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.
10.3. Possibility of hazardous reactions
None known.
10.4. Conditions to avoid
Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.
10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.
10.6. ▼Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
▼Acute toxicity

Product/substance	propan-2-ol isopropyl alcohol isopropanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5045 mg/kg ·

Product/substance	propan-2-ol isopropyl alcohol isopropanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	12800 mg/kg ·

Product/substance	propan-2-ol isopropyl alcohol isopropanol

Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	30 mg/m3 ·

Product/substance	butane
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	658000 mg/m3 ·

Based on available data, the classification criteria are not met.

Skin corrosion/irritation
Based on available data, the classification criteria are not met.

Serious eye damage/irritation
Causes serious eye irritation.

Respiratory sensitisation
Based on available data, the classification criteria are not met.

Skin sensitisation
Based on available data, the classification criteria are not met.

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Based on available data, the classification criteria are not met.

Reproductive toxicity
Based on available data, the classification criteria are not met.

STOT-single exposure
May cause drowsiness or dizziness.

STOT-repeated exposure
Based on available data, the classification criteria are not met.

Aspiration hazard
May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects
Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼Endocrine disrupting properties
This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information
propan-2-ol isopropyl alcohol isopropanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	propan-2-ol isopropyl alcohol isopropanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	13299 mg/l ·

Product/substance	propan-2-ol isopropyl alcohol isopropanol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	4200 mg/l ·

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability
Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential
Based on available data, the classification criteria are not met.

12.4. Mobility in soil
No data available.

12.5. Results of PBT and vPvB assessment
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼Endocrine disrupting properties
This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects
This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. ▼Waste treatment methods
Product is covered by the regulations on hazardous waste. (*)
To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.
HP 3 - Flammable
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14 – Ecotoxic
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code
20 01 13*	Solvents
15 01 04	Metallic packaging

Contaminated packing
Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	Yes	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	Yes	Limited quantities: 1 L EmS: F-D S-U See below for additional

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
						information.
IATA	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	Yes	See below for additional information.

* Packing group

** Environmental hazards

▼Additional information

This product is within scope of the regulations of transport of dangerous goods.
Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.
-
ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.
People under the age of 18 shall not be exposed to this product.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)
E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

REACH, Annex XVII

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics is subject to UK-REACH restrictions (entry 40).
propane is subject to UK-REACH restrictions (entry 40).
propan-2-ol isopropyl alcohol isopropanol is subject to UK-REACH restrictions (entry 40).
butane is subject to UK-REACH restrictions (entry 40).
isobutane is subject to UK-REACH restrictions (entry 40).

Additional information

Not applicable.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.
The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).
Control of Major Accident Hazards (COMAH) Regulations 2015.
2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle

Refinishing Products Regulations 2012.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.
H220, Extremely flammable gas.
H225, Highly flammable liquid and vapour.
H280, Contains gas under pressure; may explode if heated.
H304, May be fatal if swallowed and enters airways.
H319, Causes serious eye irritation.
H336, May cause drowsiness or dizziness.
H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)
LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC 7 = Industrial spraying
PROC 11 = Non industrial spraying

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

S. Grade

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en