

Masking Tape (Crepe)



Description

General purpose masking tape made of crepe paper backing coated with natural rubber adhesive. Offers excellent hand-tearability with easy straight-line tearing. Commonly used in home improvement and paint masking applications.

Application

Suitable for masking in indoor decoration, painting, signage, electrical appliances and electronics industries.

Features

- High peel strength
- Sticks well to uneven surfaces
- Easy to tear by hand, straight tear

Article number	Description	Pcs / carton
9-100-0019	19 mm × 40 m	72
9-100-0025	25 mm × 40 m	48
9-100-0038	38 mm × 40 m	60
9-100-0050	50 mm × 40 m	24

TECHNICAL DATA

Backing	Crepe paper
Adhesive	Natural rubber
Total thickness	0.12 mm ± 0.01 mm (120 µm ± 10 µm) / 4.7 mil ± 0.4 mil Test method: PSTC-133 / ASTM D 3652
Adhesion to steel	≥ 5 N/25 mm (≥ 18.3 oz/in) Test method: PSTC-101 / ASTM D 3330
Tensile strength	≥ 60 N/25 mm (≥ 13.5 lb/in) Test method: PSTC-131 / ASTM D 3759
Elongation	≥ 6 % Test method: PSTC-131 / ASTM D 3759
Holding power (2.5 cm × 2.5 cm × 1 kg)	≥ 10 h Test method: PSTC-107 / ASTM D 3654
Service temperature range	0 ~ 60 °C (32 ~ 140 °F)

SURFACE PREPARATION

As with all pressure-sensitive tapes, application surfaces must be clean, dry and free from oils, grease or any contaminants.

STORAGE

Store at 15 – 30 °C (59 – 86 °F) with relative humidity < 70 %, protected from direct sunlight and moisture.

Shelf life: 12 months from the date of manufacture when stored under recommended conditions.

NOTE

The data is based on the manufacturer's test results and is for reference only. Due to the diversity of materials and the complexity of application environments, no warranty is given regarding suitability for any specific use. Customers must verify suitability for their intended application before use.